



**ALLIANCE  
 AGRICULTURE**

TRA: **F-2**  
 Speed Rating: **A8**

Alliance 303 Steering Wheel tire is a 3-rib (front wheel) tire designed for general farming purposes. It has a raised centre rib to ensure easy steering. The tire is engineered for quiet rolling and long lasting performance in both on and off-the-road service. The strong nylon construction and use of high grade compounds make it a top quality tire.

**TRACTOR HEAVY DUTY - 9.00-16HD**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
		SW mm	OD mm					Speed							
								10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	50 kmph
9.00-16	<b>W8</b> W7 6.00F	234	855	394	2556	8PR	1.5	1070	1020	960	820	710	640	570	520
						111A6 103A8	2.3	1380	1320	1240	1060	920	830	740	670
							3.1	1640	1560	1470	1250	1090	980	870	800
						10PR	3.3	1700	1620	1530	1300	1130	1020	900	820
						116A6 108A8	3.6	1790	1700	1610	1370	1190	1070	950	870
							3.9	1880	1790	1690	1440	1250	1130	1000	910

Note: For above mentioned size only 10 PR is active for production. Recommended rim in red (Bold). Highlighted column indicates 1) 6PR and above with a 25% increase in inflation pressure. 2) In case where front-end loader is fitted on the tractor, =100% applies.

For ATC Tires Pvt Limited



Dan Steltmann  
 Chief Technology Officer

