



**GALAXY
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **A6**



TEXTILE(T) Standard
 Compound

The Galaxy Agri-Trac II has a modern, curved 45 degree lug design for both smooth riding on the road, and excellent traction in all field conditions. Its special stepped surfaces between lugs facilitate cleaning in very muddy conditions. The wide nose bar provides extra life on hard surfaces/roadwork. The Agri Trac II has been reinforced with a wear resistant compound to give it long wear capabilities. The Agri Trac II has been selected as an OEM fitment tire by leading tractor manufacturers.

TRACTOR - 18.4-30

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
		SW inch	OD inch					Speed							
								Tractor Applications							
								Static mph	6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph
18.4-30	W16LX30 DW16AX30, W15LX30 DW15AX30	18.4	61.0	27.2	179.8	8	12	9280	5640	5250	4850	4320	4030	3840	3640
						139A6 135A8	17	11770	7170	6660	6130	5470	5120	4850	4610
							19	12320	7500	6970	6440	5730	5360	5090	4830

E-Marking Number: E11 106R-002004

