



- Zigzag grooves design increase the lateral contact area. AT-5 provides the friction performance on mud, snow and gravel roads, and increase the driving force on poor road.
- Center rib interlocked pattern design to enhance stability.
- To avoid the gravel remains in the grooves and damage the tire, the stepped center sub grooves wall design with polygon edge can pop up with gravel.
- To get rid of mud and gravel, the stone ejector designed for the main grooves bottom and groove wall at the shoulder.
- To balance and avoid abnormal tire wear, the connecting bar design between patterns can enhance the pattern block rigidity.
- The AT-5 with high amount of silica can increase the stability on snow condition.

AT-5 Size List

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL		
								RRC	Wet Grip	Noise Class
45'	20	275/65R20	110(WL)	S	9	786	273	N/A	N/A	N/A
	20	285/60R20	116(WLXL)	T	9	794	297	N/A	N/A	N/A
	20	285/50R20	116(XL)	T	9	794	297	N/A	N/A	N/A
	20	265/50R20	112(WLXL)	T	8.5	774	277	N/A	N/A	N/A
55'	20	265/50R20	112(XL)	T	8.5	774	277	N/A	N/A	N/A
	20	275/55R20	117(XL)	T	8.5	810	284	N/A	N/A	N/A
	18	255/55R18	109(OV)	T	8	737	265	N/A	N/A	N/A
	20	275/60R20	115	T	8	838	279	N/A	N/A	N/A
60'	18	285/60R18	116	H	8.5	799	292	N/A	N/A	N/A
	18	285/60R18	116(WL)	H	8.5	799	292	N/A	N/A	N/A
	18	265/60R18	110	T	8	775	272	N/A	N/A	N/A
	18	265/60R18	110(WL)	H	8	775	272	N/A	N/A	N/A
65'	18	235/60R18	112(XL)	H	7.5	763	260	N/A	N/A	N/A
	18	235/60R18	112(OV)	H	7	739	240	N/A	N/A	N/A
	17	235/60R17	102(OV)	T	7	714	240	N/A	N/A	N/A
	16	235/60R16	104(XL)	H	7	688	240	N/A	N/A	N/A
70'	15	275/60R15	107(OV)	S	8	711	279	N/A	N/A	N/A
	15	265/60R15	102(OV)	S	7.5	667	260	N/A	N/A	N/A
	15	235/60R15	98(OV)	S	7	663	240	N/A	N/A	N/A
	18	275/65R18	116(OV)	T	8	815	279	N/A	N/A	N/A
75'	18	265/65R18	114(OV)	T	8	801	272	N/A	N/A	N/A
	17	265/65R17	112(WL)	T	8	776	272	N/A	N/A	N/A
	17	265/65R17	112(OV)	T	8	776	272	N/A	N/A	N/A
	17	255/65R17	114(XL)	T	7.5	764	260	N/A	N/A	N/A
VAN	17	245/65R17	111(OVXL)	T	7	750	248	N/A	N/A	N/A
	15	3111.05OR15LT	103(OV)	S	8.5	775	268	N/A	N/A	N/A
	15	309.50R15LT	104(OV)	S	7.3	750	240	N/A	N/A	N/A
	16	235/65R16C	115/113	Q	7	712	240	N/A	N/A	N/A
15	225/70R15C	112/110(OV)	S	6.5	697	228	N/A	N/A	N/A	

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL		
								RRC	Wet Grip	Noise Class
70'	18	265/70R18	114(OV)	S	8	829	272	N/A	N/A	N/A
	17	285/70R17	117	T	8.5	832	292	N/A	N/A	N/A
	17	285/70R17	117(WL)	T	8.5	832	292	N/A	N/A	N/A
	17	265/70R17	115(OV)	T	8	804	272	N/A	N/A	N/A
	17	285/70R17	112	T	7.3	790	260	N/A	N/A	N/A
	17	245/70R17	112(OVXL)	T	7	776	248	N/A	N/A	N/A
	17	235/70R17	109(XL)	T	7	762	240	N/A	N/A	N/A
	16	265/70R16	112(OV)	T	8	778	272	N/A	N/A	N/A
	16	255/70R16	112(OV)	S	7.5	764	260	N/A	N/A	N/A
	16	245/70R16	111(OVXL)	S	7	750	248	N/A	N/A	N/A
	15	265/70R15	112(OV)	S	8	753	272	N/A	N/A	N/A
	75'	16	265/75R16	116(OV)	T	7.5	804	267	N/A	N/A
15		235/75R15	109(OVXL)	T	6.5	733	235	N/A	N/A	N/A
* 20		LT2305/65R20	121/118	S	9.5	844	316	N/A	N/A	N/A
* 20		LT295/65R20	129/126	Q	8.5	893	297	N/A	N/A	N/A
* 20		LT295/65R20	121/118	Q	8.5	892	299	N/A	N/A	N/A
* 20		LT295/60R20	126/123	R	8.5	862	299	N/A	N/A	N/A
* 20		LT295/60R20	121/117	Q	8.5	862	299	N/A	N/A	N/A
* 20		LT295/65R20	123/120	Q	9.5	832	309	N/A	N/A	N/A
* 20		LT295/65R20	121/118	Q	9.5	832	309	N/A	N/A	N/A
* 20		LT285/60R20	125/122	R	8.5	850	290	N/A	N/A	N/A
* 20		LT285/65R20	121/119	Q	8.5	850	292	N/A	N/A	N/A
4WD		* 20	LT285/55R20	117/114	S	8	822	297	N/A	N/A
	* 20	LT295/65R20	126/123(OV)	S	8	866	279	N/A	N/A	N/A
	* 20	35112.50R20LT	121(OV)	S	10	877	318	N/A	N/A	N/A
	* 18	LT285/70R18	129/126	Q	8.5	871	299	N/A	N/A	N/A
	* 18	LT285/75R18	119/116	Q	8	885	286	N/A	N/A	N/A
	* 18	LT285/75R18	129/126	Q	8	885	286	N/A	N/A	N/A
	* 18	LT285/65R18	121/118	Q	8	885	286	N/A	N/A	N/A
	* 18	LT275/70R18	125/122(OV)	R	8	843	279	N/A	N/A	N/A
	* 18	LT275/70R18	121/118(OV)	Q	8	843	279	N/A	N/A	N/A
	* 18	LT275/65R18	123/120(OV)	Q	8	815	279	N/A	N/A	N/A
	* 18	LT275/65R18	119/116(OV)	Q	8	815	279	N/A	N/A	N/A
	VAN	18	LT265/70R18	124/121(OV)	S	8	829	272	N/A	N/A
18		LT265/70R18	121/118(OV)	Q	8	829	272	N/A	N/A	N/A
* 18		35112.50R18LT	123	S	10	877	318	N/A	N/A	N/A
* 18		35112.50R18LT	118	Q	10	877	318	N/A	N/A	N/A
* 18		33112.50R18LT	118	Q	10	832	318	N/A	N/A	N/A
17		LT315/50R17	121/118	S	9.5	874	323	N/A	N/A	N/A
17		LT285/75R17	121/118(OV)	S	8	860	286	N/A	N/A	N/A
17		LT285/70R17	121/118(OV)	S	8.5	832	292	N/A	N/A	N/A
* 17		LT285/70R17	121/118(OV)	S	8	804	272	N/A	N/A	N/A
* 17		LT285/70R17	121/118(OV)	Q	8	804	272	N/A	N/A	N/A
* 17		LT265/65R17	120/117(OV)	S	8	776	272	N/A	N/A	N/A
* 17		LT245/75R17	121/118(OV)	S	7	800	248	N/A	N/A	N/A
* 17	LT245/75R17	119/116(OV)	S	7	776	248	N/A	N/A	N/A	
* 17	LT235/60R17	120/117(OV)	R	6.5	808	235	N/A	N/A	N/A	
* 17	37112.50R17LT	129	Q	10	928	318	N/A	N/A	N/A	
* 17	35112.50R17LT	121	S	10	877	318	N/A	N/A	N/A	
16	LT1315/75R16	121/118	S	8.5	878	313	N/A	N/A	N/A	
16	LT285/75R16	122/118(OV)	Q	8	834	286	N/A	N/A	N/A	
16	LT285/75R16	116/113(OV)	Q	8	834	286	N/A	N/A	N/A	
* 16	LT265/75R16	123/120(OV)	Q	7.5	804	267	N/A	N/A	N/A	
* 16	LT265/75R16	119/116(OV)	Q	7.5	804	267	N/A	N/A	N/A	
* 16	LT245/75R16	120/116(OV)	R	7	774	248	N/A	N/A	N/A	
* 16	LT235/65R16	120/116(OV)	R	6.5	806	235	N/A	N/A	N/A	
* 16	LT225/75R16	115/112	S	6	744	223	N/A	N/A	N/A	
* 16	LT215/65R16	115/112	S	6	772	214	N/A	N/A	N/A	
15	LT235/55R15	104/101(OV)	S	6.5	733	235	N/A	N/A	N/A	
15	LT215/65R15	100/97(OV)	S	6	703	216	N/A	N/A	N/A	
15	35112.50R15LT	108(OV)	S	10	898	318	N/A	N/A	N/A	
15	32111.50R15LT	115(OV)	S	9	801	290	N/A	N/A	N/A	
15	31110.50R15LT	103(OV)	S	8.5	775	268	N/A	N/A	N/A	
15	309.50R15LT	104(OV)	S	7.3	750	240	N/A	N/A	N/A	
16	235/65R16C	115/113	Q	7	712	240	N/A	N/A	N/A	
15	225/70R15C	112/110(OV)	S	6.5	697	228	N/A	N/A	N/A	