




**GALAXY  
 AGRICULTURE**

TRA: **R-1**  
 Speed Rating: **A1**



Optimised 45 degree lug angle ensures good roadability while on the road and superior self cleaning in the field. Tire life is enhanced by compound designed for low wear, additional rubber at lug centre, stabilised lugs at centre by evenly distributed tie bar. Specially designed lug angles and radius prevents lug base cracks. Additional rubber layer improves penetration resistance. Tougher sidewall provides deflection stability and protection from external damages.

**TRACTOR - 12.4-24**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
								Speed										
		SW inch	OD inch					Drive Wheel (Tractor) application										
								Static mph	3 mph	6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph
12.4-24	W11X24 W10X24, W10HX24	12.4	45.7	21.4	136.5	12 129	12	4170	2890	2560	2270	2090	1870	1810	1740	1700	1630	1540
							23	6240	4320	3810	3400	3110	2820	2710	2600	2540	2430	2320
							35	7920	5470	4830	4320	3970	3570	3440	3310	3220	3090	2930
							46	9390	6480	5730	5120	4700	4230	4080	3920	3810	3660	3460
							52	10030	6950	6130	5470	5030	4520	4370	4210	4080	3920	3700

