



**GALAXY
 EARTHMOVER**

TRA: **E-3/L-3**
 Speed Rating: **A2**



CUT
 RESISTANT
 COMPOUND

LDSR 300 is specially constructed for wheel loaders operating in the toughest environments. Transportation of heavy load demands excellent stability and robustness. Sturdy radial construction coupled with strong sidewall protector provides LDSR 300 superior strength and endurance to withstand challenging terrains. Premium tread compounds provide excellent protection against lug-tearing and chunking, helping the machine to perform efficiently without any downtime. An “S-shaped” tread pattern with stepped lugs ensure optimal traction and enhanced self-cleaning assuring high productivity.

EARTHMOVER - 26.5R25

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		SW mm	OD mm					Speed									
								Load capacity for Loader Application									
								Static kmph	Creep kmph	5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph	
26.5R25	22.00/3.0	678	1735	755	5260	209A2	6.5	29600	24050	21100	18500	16100	15550	14800	14250	12950	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
		SW mm	OD mm					Speed											
								Load capacity for Earthmover application kg (lbs)											
								15 kmph	20 kmph	25 kmph	30 kmph	35 kmph	40 kmph	45 kmph	50 kmph	55 kmph	60 kmph	65 kmph	
26.5R25	22.00/3.0	678	1735	755	5260	193B	5.25	12900	12700	12400	12200	12000	11800	11700	11500	11300	10800	10100	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

