



**GALAXY  
 EARTHMOVER**

TRA: **G-2/L-2**  
 Speed Rating: **A8**

MGSR 200 is specially designed for grader applications. The unique tread pattern provides excellent traction and grip on uneven surfaces. Special compound formulation assures minimum heat-build up and maximum protection against damages. Sturdy construction with sidewall protector provides increased productivity and zero downtime making MGSR 200 the perfect choice as the partner for non-stop work.

**EARTHMOVER - 20.5R25**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		Speed												
		Load capacity for Grader application												
		15 kmph	20 kmph					25 kmph	30 kmph	35 kmph	40 kmph			
20.5R25	17.00/2.0	521	1493	660	4490	161A8	3	4625	4625	4625	4625	4625	4625	4625

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		Speed															
		Load capacity for Loader application															
		Static kmph	Creep kmph					5 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph			
20.5R25	17.00/2.0	521	1493	660	4490	186A2	5	15200	12400	10800	9500	8300	8000	7600	7300	6700	

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

