



MAXAM

MS203

E2/G2/L2

Non-directional pattern designed to maximize traction in soft underfoot conditions. Ideal for use on graders, loaders, and earthmovers.

- All steel radial tire construction maximizes traction and flotation
- Wear and cut resistant tread compound
- Self-cleaning tread design

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
14.00R24	★	TL	10.00VA	54.0	14.8	32	80	15200	69	9100	175A2/157B
				1371	376	25	550	6900	475	4125	
17.5R25	★	TL	14.00/1.5	53.1	17.5	35	73	15700	54	9100	176A2/157B
				1348	445	28	500	7100	375	4125	
20.5R25	★	TL	17.00/2.0	58.5	20.5	39	73	20900	54	12300	186A2/168B
				1486	521	31	500	9500	375	5600	
23.5R25	★	TL	19.50/2.5	63.1	23.9	43	73	26800	54	15700	195A2/176B
				1603	607	34	500	12150	375	7100	

