



MAXAM

MS300

E3/L3

Light duty E3/L3 lug pattern ideally suited to municipalities, small sand and aggregate operations as well as other smooth surface applications.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	
15.5R25	★★	TL	12.00/1.3	50.2	15.3	30	94	15700	76	9900	176A2/160B
				1274	389	24	650	7100	525	4500	
17.5R25	★★	TL	14.00/1.5	53.0	17.3	32	94	18700	76	12000	182A2/167B
				1346	440	25	650	8500	525	5450	
20.5R25	★★	TL	17.00/2.0	58.4	20.6	36	94	25400	76	16100	193A2/177B
				1493	524	28	650	11500	525	7300	
23.5R25	★★	TL	19.50/2.5	63.2	23.7	40	94	32000	76	20400	201A2/185B
				1605	601	32	650	14500	525	9250	
26.5R25	★★	TL	22.00/3.0	68.7	26.5	44	94	40800	76	25400	209A2/193B
				1739	669	35	650	18500	525	11500	
29.5R25	★★	TL	25.00/3.5	73.5	29.5	48	94	49400	76	30900	216A2/200B
				1866	751	38	650	22400	525	14000	

