



**MAXAM**

# MS301

**E3/L3**

Standard E3/L3 rock lug pattern combines excellent traction and high resistance to wear and cutting.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- High quality casing allows for excellent retreadability
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear
- Increased net-to-gross for improved tread life

Applications:



| Size    | Rating | Type | Rim       | O.D.     | S.W      | T.D.        | Infl. P.   | L.C.C.<br>(lbs/kg) | Infl. P.   | L.C.C. (lbs/<br>kg) | L.I.       |
|---------|--------|------|-----------|----------|----------|-------------|------------|--------------------|------------|---------------------|------------|
|         |        |      |           | in<br>mm | in<br>mm | 32nds<br>mm | psi<br>KPa | 5 mph<br>10 kph    | psi<br>KPa | 30 mph<br>50 kph    |            |
| 17.5R25 | ★★     | TL   | 14.00/1.5 | 52.7     | 17.7     | 35          | 94         | 18700              | 76         | 12000               | 182A2/167B |
|         |        |      |           | 1339     | 449      | 28          | 650        | 8500               | 525        | 5450                |            |
| 20.5R25 | ★★     | TL   | 17.00/2.0 | 59.0     | 20.4     | 37          | 94         | 25400              | 76         | 16100               | 193A2/177B |
|         |        |      |           | 1499     | 517      | 30          | 650        | 11500              | 525        | 7300                |            |
| 23.5R25 | ★★     | TL   | 19.50/2.5 | 63.4     | 23.9     | 41          | 94         | 32000              | 76         | 20400               | 201A2/185B |
|         |        |      |           | 1611     | 608      | 33          | 650        | 14500              | 525        | 9250                |            |
| 26.5R25 | ★★     | TL   | 22.00/3.0 | 68.8     | 26.7     | 45          | 94         | 40800              | 76         | 25400               | 209A2/193B |
|         |        |      |           | 1748     | 679      | 36          | 650        | 18500              | 525        | 11500               |            |
| 29.5R25 | ★★     | TL   | 25.00/3.5 | 74.3     | 30.0     | 49          | 94         | 49400              | 76         | 30900               | 216A2/200B |
|         |        |      |           | 1886     | 763      | 39          | 650        | 22400              | 525        | 14000               |            |

