



MAXAM

MS501

MINEXTRA - L5

For use in the most severe applications where traction and long tread life are required.

- Specialized mining compound for increased cut and impact resistance
- Extra deep L5 offset lug pattern combines excellent traction and high resistance to wear in all off-road conditions
- Deep undertread for improved puncture resistance
- Reinforced bead, shoulder, and sidewall for increased cut resistance

Applications:



| Size | Rating | Type | Rim | O.D. | S.W | T.D. | Infl. P. | L.C.C. (lbs/kg) | L.I. |
|----------|--------|------|-----------|----------|----------|-------------|------------|-----------------|-------|
| | | | | in mm | in mm | 32nds mm | psi KPa | 5 mph 10 kph | |
| 17.5R25 | ★★ | TL | 14.00/1.5 | 54.9 | 17.5 | 83 | 94 | 18700 | 182A2 |
| | | | | 1395 | 445 | 66 | 650 | 8500 | |
| 20.5R25 | ★★ | TL | 17.00/2.0 | 60.9 | 20.9 | 90 | 94 | 25400 | 193A2 |
| | | | | 1548 | 531 | 72 | 650 | 11500 | |
| 23.5R25 | ★★ | TL | 19.50/2.5 | 65.6 | 23.8 | 98 | 94 | 32000 | 201A2 |
| | | | | 1665 | 605 | 78 | 650 | 14500 | |
| 26.5R25 | ★★ | TL | 22.00/3.0 | 70.6 | 26.9 | 110 | 94 | 40800 | 209A2 |
| | | | | 1794 | 684 | 87 | 650 | 18500 | |
| 29.5R25 | ★★ | TL | 25.00/3.5 | 75.6 | 30.6 | 118 | 94 | 49400 | 216A2 |
| | | | | 1920 | 777 | 94 | 650 | 22400 | |
| 29.5R29 | ★★ | TL | 25.00/3.5 | 79.1 | 31.5 | 125 | 94 | 52000 | 218A2 |
| | | | | 2010 | 800 | 99 | 650 | 23600 | |
| 35/65R33 | ★★ | TL | 28.00/3.5 | 82.1 | 36.0 | 120 | 94 | 61500 | 224A2 |
| | | | | 2085 | 914 | 95 | 650 | 28000 | |

