

# Rollnex MT-1



- The tread pattern design is aggressive and ruffless.
- The multilateral curved block of the shoulder design provides traction in multiple directions when driving.
- The interlayer tire shoulder design effectively provide undeniable traction to bite gravel and mud sand when a tire drivers on a poor road surface, thus increasing the maneuverability of the tire when driving on poor road surface.
- Its 50% groove area ratio design provide excellent traction ability on rugged road and enhances the ability to remove sediments on muddy roads.

## MT-1 Size List

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL		
								RRC	Wet Grip	Noise Value (dB)
40'	22	295/40R22	112(WLXL)	T	10.5	795	301	N/A	N/A	N/A
	18	245/40R18	97(XL)	T	8.5	653	248	N/A	N/A	N/A
	18	235/50R18	101(WLXL)	S	7.5	693	245	N/A	N/A	N/A
55'	19	235/55R19	105(WLXL)	T	7.5	741	245	N/A	N/A	N/A
	18	225/55R18	98(WL)	T	7	705	233	N/A	N/A	N/A
60'	18	225/60R18	100(WL)	T	6.5	727	228	N/A	N/A	N/A
	17	195/60R17	90(WL)	S	6	666	201	N/A	N/A	N/A
	15	185/60R15	88(WLXL)	S	5.5	603	189	N/A	N/A	N/A
65'	15	165/60R15	77(WL)	S	5	579	168	N/A	N/A	N/A
	14	185/65R14	86	H	5.5	596	189	N/A	N/A	N/A
70'	14	155/65R14	75(WL)	S	4.5	558	157	N/A	N/A	N/A
	16	235/70R16	106(WL)	S	7	735	240	N/A	N/A	N/A
80'	16	175/80R16	91(WL)	S	5	686	177	N/A	N/A	N/A
	13	145/80R13	75(WL)	S	4	562	145	N/A	N/A	N/A

## Series

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL		
								RRC	Wet Grip	Noise Value (dB)
4WD	* 26	37*13.50R26LT	114	Q	11	928	345	N/A	N/A	N/A
	* 24	35*12.50R24LT	114	Q	10	877	318	N/A	N/A	N/A
	* 22	37*13.50R22LT	128	Q	11	928	345	N/A	N/A	N/A
	* 22	35*12.50R22LT	121	Q	10	877	318	N/A	N/A	N/A
	* 22	33*12.50R22LT	114	Q	10	826	318	N/A	N/A	N/A
	* 20	LT305/65R20	121/118	Q	9.5	844	316	N/A	N/A	N/A
	* 20	LT285/65R20	122/119	P	9	822	297	N/A	N/A	N/A
	* 20	LT275/65R20	126/123	Q	8	866	279	N/A	N/A	N/A
	* 20	LT275/65R20	121/118	Q	8	866	279	N/A	N/A	N/A
	* 20	LT275/60R20	123/120(O/W)	Q	8	838	279	N/A	N/A	N/A
	* 20	LT275/60R20	123/120(O/W)	P	8	838	279	N/A	N/A	N/A
	* 20	LT275/55R20	120/117	P	8.5	810	284	N/A	N/A	N/A
	* 20	LT265/50R20	121/118	P	8.5	774	277	N/A	N/A	N/A
	* 20	38*13.50R20LT	128	Q	11	953	345	N/A	N/A	N/A
	* 20	35*12.50R20LT	121	Q	10	877	318	N/A	N/A	N/A
	* 20	33*12.50R20LT	114	Q	10	826	318	N/A	N/A	N/A
	* 18	LT285/65R18	125/122(O/W)	P	8.5	827	292	N/A	N/A	N/A
	* 18	LT275/70R18	125/122	Q	8	843	279	N/A	N/A	N/A
	* 18	LT275/70R18	121/118	Q	8	843	279	N/A	N/A	N/A
	* 18	LT275/65R18	123/120	Q	8	815	279	N/A	N/A	N/A
	* 18	LT275/65R18	119/116	Q	8	815	279	N/A	N/A	N/A
	* 18	LT265/60R18	119/116(O/W)	P	8	775	272	N/A	N/A	N/A
	* 18	35*12.50R18LT	123	Q	10	877	318	N/A	N/A	N/A
	* 17	LT315/70R17	121/118	Q	9.5	874	323	N/A	N/A	N/A
	* 17	LT295/70R17	121/118	Q	8.5	846	297	N/A	N/A	N/A
	* 17	LT265/70R17	121/118	Q	8.5	832	292	N/A	N/A	N/A
	* 17	LT265/70R17	121/118(O/W)	Q	8	804	272	N/A	N/A	N/A
	* 17	LT265/65R17	120/117(O/W)	P	8	776	272	N/A	N/A	N/A
	* 17	LT255/75R17	111/108	Q	7	814	253	N/A	N/A	N/A
	* 17	35*12.50R17LT	121	Q	10	877	318	N/A	N/A	N/A
	* 17	33*12.50R17LT	114(W/W)	Q	10	826	316	N/A	N/A	N/A
	* 16	LT315/75R16	121/118(O/W)	Q	8.5	878	313	N/A	N/A	N/A
	* 16	LT305/70R16	124/121(O/W)	Q	9	834	311	N/A	N/A	N/A
	* 16	LT305/70R16	118/115(O/W)	Q	9	834	311	N/A	N/A	N/A
	* 16	LT285/75R16	126/123	Q	8	834	286	N/A	N/A	N/A
	* 16	LT285/75R16	116/113	Q	8	834	286	N/A	N/A	N/A
	* 16	LT265/75R16	119/116(O/W)	Q	7.5	804	267	N/A	N/A	N/A
	* 16	LT265/75R16	123/120(O/W)	Q	7.5	804	267	N/A	N/A	N/A
* 16	LT265/75R16	117/114(O/W)	Q	8	778	272	N/A	N/A	N/A	
* 16	LT245/75R16	120/116(O/W)	N	7	774	248	N/A	N/A	N/A	
* 16	LT235/65R16	120/116	Q	6.5	806	235	N/A	N/A	N/A	
* 16	LT185/65R16	105/103(WL)	N	5	721	184	N/A	N/A	N/A	
* 15	LT235/75R15	104/101(O/W)	Q	6.5	733	235	N/A	N/A	N/A	
* 15	35*12.50R15LT	113	Q	10	877	318	N/A	N/A	N/A	
* 15	33*12.50R15LT	108(O/W)	Q	10	826	318	N/A	N/A	N/A	
* 15	32*11.50R15LT	113(O/W)	Q	9	801	290	N/A	N/A	N/A	
* 15	31*10.50R15LT	109(O/W)	Q	8.5	775	268	N/A	N/A	N/A	
* 15	30*9.50R15LT	104	Q	7.5	750	240	N/A	N/A	N/A	
* 14	27*8.50R14LT	95(O/W)	Q	7	674	218	N/A	N/A	N/A	
* 16	LT185/65R16	105/103(WL)	L	5	721	182	N/A	N/A	N/A	
* 15	LT235/75R15	104/101(WL)	Q	6.5	733	235	N/A	N/A	N/A	
* 15	LT215/75R15	100/97(WL)	Q	6	703	216	N/A	N/A	N/A	

## LTR

\* = 3PLY Sidewall N/A = Values are not available at the time of publication. 30