




OH-112



All position tire for Regional applications



Specially designed shoulders help in preventing heel & toe wear ensuring longer life



Optimal placement of sipes deliver improved traction and grip, thereby reducing braking distance both in dry and wet conditions



Versatile tread design with stepped ribs ensure improved handling and driving stability

Size	PR	Load Index	Speed Symbol	Maximum Load		Max. Inflation Pressure	Rim Width	Section Width	Overall Diameter	Tread Depth
				Single (kgs)	Dual (kgs)					
7.00 R16	12	117/116	L	1285	1250	90	5.50	192	777	13.0
7.50 R16	14	122/118	L	1500	1320	100	6.00	206	808	13.0
8.25 R16	16	132/130	L	2000	1900	116	6.50	225	858	14.0
9.5 R17.5	14	129/127	L	1850	1750	110	6.75	232	842	14.0
9.5 R17.5	18	143/141	J	2725	2575	125	6.75	232	842	14.0
215/75 R17.5	12	126/124	M	1700	1600	105	6.00	210	768	14.0
215/75 R17.5	16	135/133	K	2180	2060	125	6.00	210	768	14.0
225/80 R17.5	14	123/122	L	1550	1500	105	6.00	224	810	13.0

Regrooving Guidelines

Size	D: Regrooving Depth (mm)	W: Regrooving Width (mm)
7.00 R16	2.5	5.0 - 6.0
7.50 R16	2.5	5.0 - 6.0
8.25 R16	2.5	6.0 - 7.0
9.5 R17.5	2.5	7.0 - 8.0
215/75 R17.5	2.5	7.0 - 8.0
225/80 R17.5	2.5	7.0 - 8.0

