



**GALAXY
 AGRICULTURE**

TRA: I-1
 Speed Rating: **B**



STUBBLE
 GUARD

The Galaxy Rib Implement provides excellent performance for free rolling wheels on wagons, hay balers, bale racks, seeders, wind rowers and fertilizer spreaders. It helps easy steering of machinery and equipment due to the heavily grooved ribs.

IMPLEMENT - 12.5L-15SL


Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								48 kmph	
12.5L-15SL	10LB	330	819	366	2390	8PR	2.5	1361	
							3.03	1551	

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load		
		SW mm	OD mm					Speed		
								Free rolling		
								Static kmph	15 kmph	50 kmph
12.5L-15SL	10LB	320	836	371	2438	10PR	0.8	1910	950	720
							1.8	3050	1520	1150
							2.5	3680	1830	1390
							3	3100	1780	1552

For ATC Tires Pvt Limited



Dan Steltmann
 Chief Technology Officer



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load		
								Speed		
		Free rolling								
		Static kmph	15 kmph					50 kmph		
12.5L-15SL	10LB	330	819	366	2431	14PR	0.8	1800	900	680
							2.2	3230	1610	1220
							3.2	4030	2010	1520
							4.25	3600	2070	1800

For ATC Tires Pvt Limited




Dan Steltmann
 Chief Technology Officer