

Rollnex R/T



Handling

Comfort



- Center lugs designed in 4-in-1 block accounting for around 40% of tread width can enhance straight driving stability.
- Polygonal and tortuous pattern block design presents rough tread pattern style and can supply multi-directional traction while cornering.
- Zigzag lateral groove and stair-type noise-preventing bar design can reduce noise generated from vehicle moving.
- Stair-type tread pattern block design can discharge the stones lodged in grooves and upgrade wear performance in middle and late tire life.
- Interlocking tread shoulder design contributes to eject dirt and gravel, and also enhance traction performance on muddy surfaces.
- Connecting bar design among pattern blocks can strengthen block stiffness and prevent irregular tread wear.

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL			
								RRC	Wet Grip	Noise (dB)	Noise Class
50'	20	285/50R20	116(WLXL)	T	9	794	297	D	C	75	B
	20	265/50R20	112(WLXL)	T	8.5	774	277	D	C	73	B
	16	245/70R16	111(WWXL)	S	7	750	248	D	C	72	B
70'	*18	L265/60R18	119/118(WW)	Q	8	775	272				N/A
	*17	L285/70R17	121/118(WW)	Q	8.5	832	292				N/A
	*17	L265/70R17	121/118(WW)	Q	8	804	272				N/A
	*17	L265/65R17	120/117(WW)	Q	8	776	272				N/A
4WD	*16	L285/75R16	125/123(WW)	K	8	834	286				N/A
	*16	L285/75R16	125/123(WW)	N	8	834	286				N/A
	*16	L265/75R16	112/108(WW)	Q	7.5	804	267				N/A
	*16	L265/75R16	123/120(WW)	Q	7.5	804	267				N/A
	*16	L265/70R16	117/114(WW)	Q	8	778	272				N/A
	*16	L245/75R16	120/118(WW)	Q	7	774	248				N/A

* = 3PLY Sidewall N/A = Values are not available at the time of publication.

RT Size List

Rollnex FT-9



Loading



- Interlocking shoulder block design can grip and exclude stones and clogs to increase maneuverability, and allow the car to be navigated freely on rugged roads.
- Hook-shaped blocks increase gripping thrust on creases and clogs.
- The extended blocks on tread shoulders provide extra traction between blocks and creases.
- The prominent bar on the bottom of the grooves prevents stones are lodged in the grooves. Lodged stones will be expelled by the flexible moves between the prominent bar and the groove wall.
- Z-shaped zigzag grooves mill the clogs and adopt to all kinds of rugged roads.

FT-9 Size List

Series	Inch	Size	Load Index	Speed Index	Rim Width (Inch)	OD (mm)	SW (mm)	EU TIRE LABEL			
								RRC	Wet Grip	Noise (dB)	Noise Class
55'	18	235/65R18	104(WL)	T	7.5	715	245				N/A
	17	225/60R17	99(WL)	T	6.5	702	228				N/A
	16	215/60R16	96(WLXL)	T	6.5	684	221				N/A
60'	16	205/60R16	96(WLXL)	T	6	632	209				N/A
	16	175/60R16	82(WL)	H	5	616	177				N/A
	15	185/60R15	88(WLXL)	H	5.5	603	189				N/A
	15	185/60R15	88(WL)	H	5.5	603	189				N/A
65'	15	165/60R15	77	S	5	579	168				N/A
	15	165/60R15	77(WL)	S	5	579	168				N/A
	17	245/65R17	111(WLXL)	T	7	750	248				N/A
	16	195/65R16	82	S	6	660	201				N/A
	15	195/65R15	81(WL)	S	5	595	170				N/A
	14	165/65R14	73(WL)	S	5	570	170				N/A
70'	13	155/65R13	73(WL)	S	4.5	532	157				N/A
	16	225/70R16	103(WL)	S	6.5	722	228				N/A
	16	215/70R16	100(WL)	T	6.5	708	221				N/A
	15	205/70R15	96	Q	6	669	209				N/A
	13	155/70R13	75(WL)	S	4.5	548	156				N/A
	16	205/60R16	104(WLXL)	T	5.5	734	203				N/A
80'	16	175/80R16	91(WL)	S	5	686	177				N/A

* = 3PLY Sidewall N/A = Values are not available at the time of publication.