



**GALAXY  
CONSTRUCTION &  
INDUSTRIAL**

TRA: **E-3**  
Speed Rating: **A2**



CUT & CHIP  
RESISTANT  
COMPOUND

S-300 E-3/L-3 is the latest addition to Galaxy 's range of construction and mining tires. It is designed keeping in mind the versatility of the terrains on which these machines ply ranging from soft muddy soil to gravelly rocky terrain. The advanced S pattern promises exceptional traction, excellent stability and durability which ensures maximum productivity.

**Bias Earthmover - 16/70-20 (405/70-20)**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load
		SW mm	OD mm					Speed
								Load Capacity (For Loader Application)
								10 kmph
16/70-20	13x20	405	1090	490	3255	16PR	4.5	5800

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load
		SW mm	OD mm					Speed
								Load Capacity (For Earthmoving Application)
								50 kmph
16/70-20	13x20	405	1090	490	3255	16PR	3.5	3350

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

