



SR2000

ALL-TERRAIN TIRE



Special Tread Compound and Block Design

Optimally blended Special compound reduces chip and tear for superior gravel road endurance. Block design provides increased tread block stability, for better even wear over the long haul.



3D Sipe

3D active sipe technology provides snow traction and increase grip.



Concave Shoulder

Concave shoulder blocks provides greater performance in soft soil and deep snow conditions.



Thicker Shoulder

Increase rubber thickness on the shoulder reduces the risk of damage and perforation, also increases mud, snow and rock traction.

SA2000

ALL-TERRAIN TIRE

Size	Ply Rating	LI/SS	BSW/WL	Max. Load (kg/lbs)		Rim Width	Max. Inflation Pressure
				Single	Dual	Inch	kPa/psi
265/70R16	-	112S	BSW	1120 / 2469	-	8.00	300 / 44
265/75R16	-	116R	BSW	1250 / 2756	-	7.50	300 / 44
265/65R17	-	116S XL	BSW	1250 / 2756	-	8.00	340 / 50
265/60R18	-	110S	BSW	1060 / 2337	-	8.00	300 / 44
265/50R20 *	-	111Q XL	BSW / WL	1090 / 2403	-	8.50	340 / 50
265/50R20	-	111S XL	BSW	1090 / 2403	-	8.50	340 / 50
LT245/70R16 *	10	118/115Q	BSW / WL	1320 / 2910	1215 / 2680	7.00	550 / 80
LT245/70R16	8	113/110S	BSW	1150 / 2535	1060 / 2335	7.00	450 / 65
LT265/70R16 *	10	121/118Q	BSW / WL	1450 / 3195	1320 / 2910	8.00	550 / 80
LT265/75R16 *	8	119/116Q	BSW / WL	1360 / 3000	1250 / 2755	7.50	450 / 65
LT265/75R16	10	123/120R	BSW	1550 / 3415	1400 / 3085	7.50	550 / 80
LT265/65R17 *	10	120/117Q	BSW / WL	1400 / 3085	1285 / 2835	8.00	550 / 80
LT265/60R18 *	10	119/116Q	BSW / WL	1360 / 3000	1250 / 2755	8.00	550 / 80
LT285/65R18 *	8	121/118Q	BSW / WL	1450 / 3195	1320 / 2910	8.50	450 / 65
LT285/65R18	10	125/122R	BSW	1650 / 3640	1500 / 3305	8.50	550 / 80
LT275/55R20 *	10	120/117Q	BSW / WL	1400 / 3085	1285 / 2835	8.50	550 / 80
LT275/55R20	10	120/117S	BSW	1400 / 3085	1285 / 2835	8.50	550 / 80

Variation: BSW : Black sidewall
 WL : White letter

Remark: *POR (Professional Off Road)