

# S811

MIXED SERVICE STEER / ALL POSITION – 5 sizes

ALL-POSITION



Size	LRP	LI	SS	OD	OW	SLR	RM	MRL Single	MRL Dual	F	W	NR (dB)	NG
				mm	mm	mm	in	(kg@kPa)	(kg@kPa)				
8.25R20	16	139/137	K	974	236	452	6.5	2430@930	2300@930	*	*	*	*
9.00R20	16	144/142	K	1019	259	471	7	2800@900	2650@900	*	*	*	*
10.00R20	18	149/146	K	1054	278	486	7.5	3250@930	3000@930	*	*	*	*
11.00R20	18	152/149	K	1085	293	499	8	3550@930	3250@930	*	*	*	*
12.00R20	18	154/149	K	1125	315	516	8.5	3790@840	3270@770	*	*	*	*

\*Not Applicable

- Tread pattern pitch design reduces ride noise.
- Enhanced tread bead design provides excellent load capability.
- Closed shoulder design provides excellent stability and reduces shoulder wear.
- Low rolling resistance compounds and construction for superb fuel economy.
- Rib siping design improves overall traction in wet conditions.
- Three wide grooves provide excellent grip and all-season performance.



The design and angle of the major grooves and groove bottoms provide a strong grip and traction



Three main longitudinal grooves provide good directional stability and reduce irregular wear



Excellent resistance to puncture and to abrasion

