



Does this tire fit? Check now:



BY VEHICLE



BY TIRE SIZE



BY PLATE

ContiSportContact 3 SPECIFICATIONS

Find Tire Size



+ 235/40 R 18

Load Index	91	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3578630000	Approved Rim Width	(8.0 - 9.5) in	Tire Diameter	25.4 in
Tire Weight	22 lbs	Max Load	1356 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	9.5 (8.5) in	Tread Depth	10/32 in	Tire Metric	Metric
Load Range	SL	Revs Per Mile	818	UTQG	280 AA A		

+ 245/35 ZR 20

Load Index	95	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3564410000	Approved Rim Width	(8.0 - 9.5) in	Tire Diameter	26.8 in
Tire Weight	24.7 lbs	Max Load	1521 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	9.8 (8.5) in	Tread Depth	10/32 in	Tire Metric	Metric
Load Range	XL	Revs Per Mile	777	UTQG	280 AA A		

+ 245/40 ZR 20

Load Index	99	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3579040000	Approved Rim Width	(8.0 - 9.5) in	Tire Diameter	27.7 in
Tire Weight	26.7 lbs	Max Load	1709 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	9.8 (8.5) in	Tread Depth	9/32 in	Tire Metric	Metric
Load Range	XL	Revs Per Mile	750	UTQG	280 AA A		

+ 245/45 R 18

Load Index	96	Speed Rating	Y	Tread Wear	280	Traction	A
Temperature	A	Article Number	3572520000	Approved Rim Width	(7.5 - 9.0) in	Tire Diameter	26.7 in
Tire Weight	31.8 lbs	Max Load	1565 lbs	Rim Protector	No	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	9.6 (8.0) in	Tread Depth	9/32 in	Tire Metric	Metric
Load Range	SL	Run Flat	Yes	Revs Per Mile	779	UTQG	280 A A

+ 255/45 ZR 19

Load Index	100	Speed Rating	(Y)	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3564170000	Approved Rim Width	(8.0 - 9.5) in	Tire Diameter	28 in
Tire Weight	26.9 lbs	Max Load	1764 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	10.0 (8.5) in	Tread Depth	9/32 in	Tire Metric	Metric
Load Range	SL	Revs Per Mile	741	UTQG	280 AA A		

+ 255/55 R 18

Load Index	109	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3590180000	Approved Rim Width	(7.0 - 9.0) in	Tire Diameter	29 in

Tire Weight	31.2 lbs	Max Load	2271 lbs	Rim Protector	Yes	Max Inflation Pressure	50 psi
Side Wall	BSW	Overall Section Width	10.4 (8.0) in	Tread Depth	10/32 in	Tire Metric	Metric
Load Range	XL	Revs Per Mile	715	UTQG	280 AA A		

+ 265/40 R 20

Load Index	104	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3579140000	Approved Rim Width	(9.0 - 10.5) in	Tire Diameter	28.3 in
Tire Weight	27.9 lbs	Max Load	1984 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	10.7 (9.5) in	Tread Depth	9/32 in	Tire Metric	Metric
Load Range	XL	Revs Per Mile	733	UTQG	280 AA A		

+ 285/35 ZR 20

Load Index	104	Speed Rating	Y	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3564430000	Approved Rim Width	(9.5 - 11.0) in	Tire Diameter	27.9 in
Tire Weight	29.8 lbs	Max Load	1984 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	11.4 (10.0) in	Tread Depth	10/32 in	Tire Metric	Metric
Load Range	XL	Revs Per Mile	746	UTQG	280 AA A		

+ 285/40 ZR 19

Load Index	103	Speed Rating	(Y)	Tread Wear	280	Traction	AA
Temperature	A	Article Number	3589860000	Approved Rim Width	(9.5 - 11.0) in	Tire Diameter	28 in
Tire Weight	31.2 lbs	Max Load	1929 lbs	Rim Protector	Yes	Max Inflation Pressure	51 psi
Side Wall	BSW	Overall Section Width	11.4 (10.0) in	Tread Depth	9/32 in	Tire Metric	Metric
Load Range	SL	Revs Per Mile	743	UTQG	280 AA A		