



BAM04

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads.



Suitable

- Wide-base tire.
- Deep tread improves wear resistance.
- Strengthened tread and carcass design improve overall tire safety.



BAM05

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads.



Suitable

- Improved wear resistance.
- Improved handling and wet skid resistance.
- Reduced stone retention.

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
VN	255/70R22.5	140/137L	16	16.0	7.50	930	255	17.13	2500	2300	830	120
CN	11.00R20	152/149K	18	16.5	8.00		293	19.65	3550	3250	930	135

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	7.00R16LT	118/114K	14	11.5	5.50F	775	200	14.25	1320	1180	770	112
CN	7.50R16LT	122/118L	14	12.5	6.00G	805	215	14.76	1500	1320	770	112
CN	7.50R16LT	125/121L	16	12.5	6.00G	805	215	14.76	1650	1450	870	125
CN	8.25R16LT	128/124L	16	14.0	6.50H	855	235	15.63	1800	1600	770	112
CN	8.25R20	139/137K	16	13.0	6.50	974	236	17.80	2430	2300	930	135
CN	9.00R20	141/139K	14	15.0	7.00	1019	259	18.54	2575	2430	790	115
CN	9.00R20	144/142K	16	15.0	7.00	1019	259	18.54	2800	2650	900	130
CN	10.00R20	149/146K	18	16.0	7.50	1054	278	19.13	3250	3000	930	135
CN	11.00R20	150/147K	16	16.5	8.00	1085	293	19.65	3350	3075	830	120
CN	11.00R20	152/149K	18	16.5	8.00	1085	293	19.65	3550	3250	930	135
CN	12.00R20	154/151K	18	17.0	8.50	1125	315	20.31	3750	3450	830	120
CN	12.00R20	158/155J	22	17.0	8.50	1125	315	20.31	4250	3875	970	140
CN	12.00R20	158/155K	22	17.0	8.50	1125	315	20.31	4250	3875	970	140
CN	11R22.5	149/146M	18	16.0	8.25	1059	279	19.33	3250	3000	930	135
CN	11R22.5	148/145M	16	16.0	8.25	1059	279	19.33	3150	2900	850	123
CN	12R22.5	152/149L	18	15.5	9.00	1085	300	19.84	3550	3250	930	135
CN	315/80R22.5	156/153L	20	16.5	9.00	1076	312	19.69	4000	3650	850	123
CN/VN	325/95R24	162/160K	22	15.5	9.00	1228	325	22.36	4750	4500	850	125