



# BAR26

### Suitable Conditions

Medium and long mileage vehicles running on paved roads.



- Excellent durability.
- Improved heat dissipation.
- Tread chunking resistance.


Suitable



# BAR49

### Suitable Conditions

Medium and long mileage vehicles running on paved roads.



- Excellent durability.
- Improved heat dissipation.
- Tread chunking resistance.

Suitable

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	9.5R17.5	143/141J	18	13.5	6.75	842	240	15.63	2725	2575	875	125
CN/VN	215/75R17.5	135/133L	16	12.5	6.00	767	211	14.17	2180	2060	865	125
CN	215/75R17.5	135/133M	16	12.5	6.00	767	211	14.17	2180	2060	865	125
CN/VN	215/75R17.5	136/134J	18	12.5	6.00	767	211	14.17	2240	2120	890	129
CN/VN	225/70R19.5	128/126L	14	12.5	6.75	811	226	15.43	1800	1700	760	110
CN/VN	225/70R19.5	128/126L	16	12.5	6.75	811	226	15.43	1800	1700	760	110
CN	225/75R17.5	129/127M	14	12.5	6.75	783	226	14.45	1850	1750	725	105
CN	225/80R17.5	123/122M	14	15.5	6.75	805	226	14.72	1550	1500	700	125
CN	225/80R17.5	123/122M	18	15.5	6.75	805	226	14.72	1550	1500	700	102
CN/VN	235/75R17.5	132/129M	16	12.5	6.75	797	233	14.69	2000	1850	830	120
CN/VN	235/75R17.5	143/141J	18	12.5	6.75	797	233	14.69	2725	2575	865	125
VN	235/75R17.5	143/141L	18	12.5	6.75	797	233	14.69	2725	2575	865	125
CN/VN	245/70R19.5	135/133M	16	13.0	7.50	839	248	15.39	2180	2060	830	120
CN/VN	245/70R19.5	136/134M	16	13.0	7.50	839	248	15.39	2240	2120	830	120
CN/VN	245/70R19.5	144/142J	18	13	7.50	839	248	15.39	2800	2650	900	130
CN/VN	255/70R22.5	140/137M	16	13.5	7.50	930	255	17.13	2500	2300	830	120
CN	265/70R19.5	143/141J	18	13.5	7.50	867	262	15.83	2725	2575	900	130
CN/VN	275/70R22.5	144/141M	16	14.5	8.25	958	276	17.56	2800	2575	830	120
CN/VN	275/70R22.5	148/145M	16	14.5	8.25	958	276	17.56	3150	2900	900	130
CN/VN	275/70R22.5	148/145M	18	14.5	8.25	958	275	17.56	3150	2900	900	130
CN	285/70R19.5	146/144M	16	13.0	8.25	895	283	16.3	3000	2800	900	130
CN	285/70R19.5	150/148K	18	13.0	8.25	895	283	16.3	3350	3150	900	130

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN/VN	275/80R22.5	149/146L	16	16.0	8.25	1012	276	18.26	3250	3000	850	123