



BDO25

Suitable Conditions
Short mileage vehicles running on unpaved roads.



- Improved heat dissipation.
- Greater tear resistance.
- Block drop-off resistance.

Suitable



BDO89

Suitable Conditions
Short mileage vehicles running on unpaved roads.



- Excellent durability.
- Improved scratch and impact resistance.
- Strong off-road traction and driving stability.

Suitable

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	12.00R20	158/155D	22	24.0	8.50	1125	315	20.31	4250		970	140

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	7.50R16LT	122/118G	14	14.5	6.00G	805	215	14.76	1500	1320	770	112
CN	8.25R16LT	128/124G	16	15.5	6.50H	865	235	15.63	1800	1600	770	112
CN	8.25R20	139/137G	16	17.0	6.50	986	236	17.80	2430	2300	930	135
CN	9.00R20	141/139F	14	20.5	7.00	1019	259	18.54	2575	2430	790	115
CN	9.00R20	144/142F	16	20.5	7.00	1030	259	18.54	2800	2650	900	130
CN	9.00R20	146/144F	18	20.5	7.00	1019	259	18.54	3000	2800	970	140
CN	10.00R20	149/146F	18	23.5	7.50	1065	278	19.13	3250	3000	930	135
VN	11.00R20	152/149F	18	24.5	8.00	1096	293	19.65	3550	3250	930	135
VN	11.00R20	150/147F	16	24.5	8.00	1096	293	19.65	3350	3075	830	120
VN	12.00R20	154/151F	18	24.5	8.50	1136	315	20.31	3750	3450	830	120
VN	12.00R20	158/155F	22	24.5	8.50	1136	315	20.31	4250	3875	970	140
CN/VN	12.00R24	160/157F	20	31.0	8.50	1238	315	22.52	4500	4125	900	130
CN	11R22.5	146/143G	16	23.5	8.25	1065	279	19.33	3000	2725	830	120
CN	11R22.5	148/145G	16	23.5	8.25	1065	279	19.33	3150	2900	850	123
CN	11R22.5	149/146G	18	23.5	8.25	1065	279	19.33	3250	3000	930	135
CN/VN	11R24.5	149/146G	16	23.5	8.25	1104	279	20.31	3250	3000	830	120
CN	12R22.5	152/149G	18	23.5	9.00	1085	300	19.84	3550	3250	930	135
CN	235/75R17.5	143/141G	16	17.0	6.75	803	233	14.69	2725	2575	860	125
CN	235/75R17.5	143/141G	18	17.0	6.75	797	233	14.69	2725	2575	875	127
CN	295/80R22.5	152/149J	18	23.5	9.00	1044	298	19.17	3550	3250	900	130
CN	315/80R22.5	156/150G	18	23.5	9.00	1076	312	19.69	4000	3350	850	123