




BDM10

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads.



- Excellent traction.
- Excellent durability.
- Tread chunking resistance.

 Suitable




BDM12

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads.



- Excellent durability.
- High strength.

 Suitable

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	12R22.5	152/149K	18	20.0	9.00	1085	300	19.84	3550	3250	930	135
VN	13R22.5	154/151K	18	22.0	9.75	1124	320	20.51	3750	3450	830	120
CN/VN	13R22.5	156/150J	20	22.0	9.75	1124	320	20.51	4000	3350	875	125
CN/VN	315/80R22.5	156/153K	20	22.0	9.00	1076	312	19.69	4000	3650	850	125

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
VN	11.00R20	150/147K	16	18.0	8.00	1085	293	19.65	3350	3075	830	120