



BDM79

Suitable Conditions

Medium and short mileage trucks running on paved and unpaved roads.



BDM82

Suitable Conditions

Medium and long mileage trucks running on paved and unpaved roads.



Suitable

- The sturdy tread blocks provide powerful traction and off-road mobility.



Suitable

- Interlocking lugs improve stability and uniform wear.
- Stone ejectors reduce stone retention.
- Wide footprint and unique shoulder design improve stability.
- Special tread compound improves tread life.

| Plant | Size | L.I. / S.R. | P.R. | T.D. mm | RIM inch | O.D. mm | S.W. mm | S.L.R. inch | L.C.C. | | | |
|-------|-----------|-------------|------|---------|----------|---------|---------|-------------|-----------|---------|----------|----------|
| | | | | | | | | | Single kg | Dual kg | A.P. kPA | A.P. PSI |
| VN | 325/95R24 | 162/160K | 22 | 20.0 | 9.00 | 1228 | 325 | 22.36 | 4750 | 4500 | 850 | 125 |

| Plant | Size | L.I. / S.R. | P.R. | T.D. mm | RIM inch | O.D. mm | S.W. mm | S.L.R. inch | L.C.C. | | | |
|-------|-------------|-------------|------|---------|----------|---------|---------|-------------|-----------|---------|----------|----------|
| | | | | | | | | | Single kg | Dual kg | A.P. kPA | A.P. PSI |
| CN | 385/65R22.5 | 160K(158L) | 20 | 16.5 | 11.75 | 1072 | 389 | 19.45 | 4500 | | 900 | 130 |
| CN | 445/65R22.5 | 168K | 20 | 16.5 | 13.00 | 1150 | 444 | 20.71 | 5600 | | 830 | 120 |