



# BDR72

### Suitable Conditions

Medium and long mileage trucks running on paved roads.



● Suitable

- Widen tread groove design improves grip.
- Tread width is designed to improve traction and reduce fuel consumption.
- The transverse sipe design improves traction on wet roads.



# BDR75

### Suitable Conditions

Medium and long mileage vehicles running on paved roads.



● Suitable

- Excellent traction.
- High wear resistance.
- Tread chunking resistance.

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	315/80R22.5	156/153K	20	19.5	9.00	1076	312	19.69	4000	3650	850	123

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	9.5R17.5	143/141J	18	16.5	6.75	842	240	15.63	2725	2575	875	125
CN	11R22.5	146/143K	16	20.0	8.25	1065	279	19.33	3000	2725	830	120
CN	12R22.5	152/149K	18	19.5	9.00	1085	300	19.84	3550	3250	930	135
CN	205/75R17.5	124/122L	14	15.0	6.00	753	205	13.90	1600	1500	750	110
CN	215/75R17.5	136/134J	18	15.0	6.00	767	211	14.17	2240	2120	890	129
CN	215/75R17.5	135/133L	16	15.0	6.00	767	211	14.17	2180	2060	860	125
CN	235/75R17.5	143/141L	18	15.0	6.75	797	233	14.69	2725	2575	860	125
CN	245/70R19.5	144/142J	18	16.0	7.50	839	248	15.39	2800	2650	900	130
CN	265/70R19.5	143/141J	18	16.0	7.50	867	262	15.83	2725	2575	900	130
CN	285/70R19.5	150/148K	18	16.0	8.25	895	283	16.30	3350	3150	900	130
VN	295/80R22.5	152/148M	18	22.0	9.00	1044	298	19.17	3550	3150	850	125
VN	295/80R22.5	152/149M	18	22.0	9.00	1044	298	19.17	3550	3250	900	130
CN/VN	315/70R22.5	156/150L	18	20.0	9.00	1014	312	18.46	4000	3350	900	130
CN	315/70R22.5	154/150L	18	20.0	9.00	1014	312	18.46	3750	3350	900	130
CN/VN	315/80R22.5	156/153L	20	22.5	9.00	1076	312	19.69	4000	3650	850	125