



BDR77

Suitable Conditions

Medium and long mileage vehicles running on paved roads.



● Suitable

- Tread block sipe design improves grip.
- Open shoulder and tread groove design reduce stone retention and improve traction.
- High strength casing for improved durability.



BDR78

Suitable Conditions

Medium and long mileage trucks running on paved roads



● Suitable

- Improved traction and braking performance.
- High wear and tear resistance.
- Improved tire mileage.

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN/VN	10R22.5	141/139M	14	18.5	7.50	1019	254	18.74	2575	2430	790	115
CN/VN	11R22.5	144/142L	14	19.5	8.25	1065	279	19.33	2800	2650	720	105
VN	11R22.5	144/142M	14	19.5	8.25	1065	279	19.33	2800	2650	720	105
CN/VN	11R22.5	146/143L	16	19.5	8.25	1065	279	19.33	3000	2725	830	120
VN	11R22.5	146/143M	16	19.5	8.25	1065	279	19.33	3000	2725	830	120
CN/VN	11R24.5	146/143L	14	19.5	8.25	1116	279	20.31	3000	2725	720	105
VN	11R24.5	146/143M	14	19.5	8.25	1116	279	20.31	3000	2725	720	105
CN/VN	11R24.5	149/146L	16	19.5	8.25	1116	279	20.31	3250	3000	830	120
VN	11R24.5	149/146M	16	19.5	8.25	1116	279	20.31	3250	3000	830	120
CN/VN	255/70R22.5	140/137L	16	19.5	7.50	930	255	17.13	2500	2300	830	120
VN	285/75R24.5	144/141L	14	19.5	8.25	1062	283	19.41	2800	2575	760	110
VN	285/75R24.5	147/144L	16	19.5	8.25	1062	283	19.41	3075	2800	830	120
VN	295/75R22.5	144/141L	14	19.5	9.00	1026	298	18.66	2800	2575	760	110
VN	295/75R22.5	146/143L	16	19.5	9.00	1026	298	18.66	3000	2725	830	120

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	315/80R22.5	156/153K	20	18.0	9.00	1076	312	19.69	4000	3650	850	125