



BFR65

Suitable Conditions

Medium and long mileage vehicles running on paved roads.



Suitable

- High wear resistance.
- Long tread life.
- Improved fuel economy.



BFR68

Suitable Conditions

Medium and short mileage trucks running on paved roads.



Suitable

- The sipe groove design improves heat dissipation, grip, and wet skid resistance.
- Groove nodules reduce stone retention.
- Tread groove design provides superior high-speed handling.

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN/VN	12R22.5	152/149L	18	17.0	9.00	1085	300	19.84	3550	3250	930	135
CN/VN	295/80R22.5	152/149M	18	16.0	9.00	1044	298	19.17	3550	3250	900	130
CN	315/60R22.5	152/148L	18	14.5	9.75	950	313	17.40	3550	3150	900	130
VN	315/70R22.5	156/150L	18	15.5	9.00	1014	312	18.46	4000	3350	900	130
CN/VN	315/80R22.5	156/153L	20	17.0	9.00	1076	312	19.69	4000	3650	850	125

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	315/80R22.5	156/153K	20	15.0	9.00	1076	312	19.69	4000		850	123