




# HH01

Excellent handling, superior comfort, high-speed stability and low running noise provide a great driving experience.



## PATTERN DESIGN & FEATURES

Product Design	Product Performance
	<p><b>Tread Elements</b></p> <p>The tread compound is designed to effectively reduce rolling resistance for an improved fuel economy. Tread pattern offers greater handling for a safer and more comfortable driving experience.</p>
	<p><b>Noise Emission</b></p> <p>The tread block pitch order and shoulder grooves effectively reduce running noise and ensure excellent performance.</p>
	<p><b>Safety</b></p> <p>The four main grooves and central rib are designed to provide excellent water drainage to improve driving performance for both wet and dry roads.</p>

## SIZES

RIM	SIZE	PR	LI	SS	XL OR NOT	SIDEWALL	STANDARD RIM	UTQG	MAX LOAD (kg)	PRESSURE (kpa)	PLANT
13	175/60R13		77	T		BSW	5.00B	420/A/A	412	300	CN
13	185/60R13		80	T		BSW	5.50B	420/A/A	450	300	CN
13	185/60R13		80	T		WR	5.50B	420/A/A	450	300	CN
13	165/65R13		77	T		BSW	5.00B	420/A/A	412	300	CN
13	165/70R13		83	T	XL	BSW	5.00B	420/A/A	487	340	CN
13	175/70R13		82	T		BSW	5.00B	420/A/A	475	300	CN
13	175/70R13		82	T		WR	5.00B	420/A/A	475	300	CN
13	185/70R13		86	T		BSW	5.50B	420/A/B	530	300	CN
14	165/60R14		75	H		BSW	5J	420/A/A	387	300	CN
14	175/60R14		79	H		BSW	5J	420/A/A	437	300	CN
14	185/60R14		82	H		BSW	5 1/2J	420/A/A	475	300	CN
14	195/60R14		86	H		BSW	6J	420/A/A	530	300	CN/VN
14	205/60R14		88	T		BSW	6J	420/A/A	560	300	CN
14	175/65R14		82	T		BSW	5J	420/A/A	475	300	CN
14	175/65R14		86	T	XL	BSW	5J	420/A/A	530	340	CN
14	175/65R14		86	T	XL	RWL	5J		530	340	CN
14	185/65R14		86	H		BSW	5 1/2J	420/A/A	530	300	CN
14	195/65R14		89	H		BSW	6J	420/A/A	580	300	CN/VN
14	165/70R14		85	T	XL	BSW	5J	420/A/A	515	340	CN
14	175/70R14		88	T	XL	BSW	5J	420/A/A	560	340	CN
14	185/70R14		88	H		BSW	5 1/2J	420/A/A	560	300	CN
14	195/70R14		91	T		BSW	6J	420/A/A	615	300	CN
14	205/70R14		95	T		BSW	6J	420/A/A	690	300	CN
14	205/70R14		98	T	XL	BSW	6J	420/A/A	750	340	CN/VN

**SIZES**

RIM	SIZE	PR	LI	SS	XL OR NOT	SIDEWALL	STANDARD RINM	UTQG	MAX LOAD (kg)	PRESSURE (kpa)	PLANT
15	195/50R15		82	V		BSW	6J	420/A/A	475	300	CN
15	185/55R15		82	V		BSW	6J	420/A/A	475	300	CN
15	195/55R15		85	V		BSW	6J	420/A/A	515	300	CN
15	185/60R15		84	H		BSW	5 1/2J	420/A/A	500	300	CN
15	185/60R15		88	H	XL	BSW	5 1/2J	420/A/A	560	340	CN
15	195/60R15		88	H		BSW	6J	420/A/A	560	300	CN
15	195/60R15		88	V		BSW	6J	420/A/A	560	300	CN
15	205/60R15		91	H		BSW	6J	420/A/A	615	300	CN
15	205/60R15		95	H	XL	BSW	6J	420/A/A	690	340	CN
15	215/60R15		94	H		BSW	6 1/2J	420/A/A	670	300	CN
15	225/60R15		96	V		BSW	6 1/2J	420/A/A	710	300	CN
15	175/65R15		84	H		BSW	5J	420/A/A	500	300	CN
15	185/65R15		88	H		BSW	5 1/2J	420/A/A	560	300	CN
15	185/65R15		92	H	XL	BSW	5 1/2J	420/A/A	630	340	CN
15	195/65R15		91	V		BSW	6J	420/A/A	615	300	CN
15	195/65R15		95	T	XL	BSW	6J	420/A/A	690	340	CN
15	205/65R15		94	H		BSW	6J	420/A/A	670	300	CN
15	205/65R15		94	V		BSW	6J	420/A/A	670	300	CN
15	215/65R15		96	H		BSW	6 1/2J	420/A/A	710	300	CN
15	215/65R15		96	V		BSW	6 1/2J	420/A/A	710	300	CN
15	205/70R15		96	T		BSW	6J	420/A/B	710	300	CN
15	215/70R15		98	H		BSW	6 1/2J	420/A/A	750	300	CN
16	195/50R16		88	V	XL	BSW	6J	420/A/A	560	340	CN
16	205/50R16		87	V		BSW	6 1/2J	420/A/A	545	300	CN
16	225/50R16		92	V		BSW	7J	420/A/A	630	300	CN/VN
16	205/55R16		91	V		BSW	6 1/2J	420/A/A	615	300	CN
16	215/55R16		97	H	XL	BSW	7J	420/A/A	730	340	CN

**SIZES**

RIM	SIZE	PR	LI	SS	XL OR NOT	SIDEWALL	STANDARD RINM	UTQG	MAX LOAD (kg)	PRESSURE (kpa)	PLANT
16	195/60R16		89	V		BSW	6J	420/A/A	580	300	CN
16	205/60R16		92	H		BSW	6J	420/A/A	630	300	CN
16	205/60R16		92	V		BSW	6J	420/A/A	630	300	CN
16	215/60R16		95	H		BSW	6 1/2J	420/A/A	690	300	CN
16	215/60R16		95	V		BSW	6 1/2J	420/A/A	690	300	CN
16	225/60R16		98	H		BSW	6 1/2J	420/A/A	750	300	CN
16	205/65R16		95	H		BSW	6J	420/A/A	690	300	CN
16	215/65R16		98	T		BSW	6 1/2J	420/A/A	750	300	CN
16	235/65R16		103	H		BSW	7J	420/A/B	875	300	CN
17	215/45R17		91	W	XL	BSW	7J	420/A/A	615	340	CN
17	225/45R17		94	W	XL	BSW	7 1/2J	420/A/A	670	340	CN
17	235/45R17		97	W	XL	BSW	8J	420/A/A	730	340	CN
17	205/50R17		89	V		BSW	6 1/2J	420/A/A	580	300	CN
17	215/50R17		91	V		BSW	7J	420/A/A	615	300	CN
17	225/50R17		94	V		BSW	7J	420/A/A	670	300	CN
17	215/55R17		94	V		BSW	7J	420/A/A	670	300	CN
17	225/55R17		97	V		BSW	7J	420/A/A	730	300	CN
17	225/55R17		97	W		BSW	7J	420/A/A	730	300	CN
17	215/60R17		96	H		BSW	6 1/2J	420/A/A	710	300	CN
17	215/60R17		96	T		BSW	6 1/2J	420/A/A	710	300	CN
17	225/60R17		99	H		BSW	6 1/2J	420/A/A	775	300	CN
17	235/60R17		102	T		BSW	7J	420/A/A	850	300	CN
17	215/65R17		99	T		BSW	6 1/2J	420/A/B	775	300	CN
18	235/40R18		95	W	XL	BSW	8 1/2J	420/A/A	690	340	CN
18	235/55R18		100	V		BSW	7 1/2J	420/A/A	800	300	CN
18	235/60R18		103	H		BSW	7J	420/A/A	875	300	CN
18	235/60R18		107	V	XL	BSW	7J	420/A/A	975	340	CN