



BTR60

Suitable Conditions

Long mileage trucks and passenger busses running on paved and highway roads.



BTR96

Suitable Conditions

Medium and long mileage vehicles running on paved roads.



Suitable

- Long tread life and great high speed stability.
- Durable and wear-resistant sidewall.
- Improved heat dissipation.
- Low noise emissions and reduced stone retention.



Suitable

- Double-wide.
- Improved heat dissipation.
- Improved skid and wear resistance.
- Reduced stone retention.
- Extended tread life.

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
VN	385/55R22.5	160K	20	14.5	12.25	996	386	18.39	4500	900	130	
CN/VN	385/65R22.5	160K	20	15.5	11.75	1072	389	19.45	4500	900	130	

Plant	Size	L.I. / S.R.	P.R.	T.D. mm	RIM inch	O.D. mm	S.W. mm	S.L.R. inch	L.C.C.			
									Single kg	Dual kg	A.P. kPA	A.P. PSI
CN	385/65R22.5	160K	20	15.5	11.75	1072	389	19.45	4500	900	130	
VN	435/50R19.5	160J	20	12.5	14.00	931	438	16.65	4500	900	130	
VN	445/45R19.5	160J	20	13.0	15.00	895	446	16.46	4500	900	130	